



INJURY PREVENTION

Quick Review of Safety

Aerial Lifts

BEST PRACTICES

- Conduct a thorough pre-start inspection based on the lift being used. Inspect the site for hazards, both on the ground and overhead.
- Always keep your feet on the floor of the platform or bucket; do not lean over or climb on guardrails.
- Never use ladders or other equipment to further extend your height from the lift platform.
- Always use fall restraint/arrest protection on the equipment that is attached to an identified location on the platform. A body harness should be worn and connected as soon as you or any other worker enters the platform or bucket.
- Always have a thorough understanding of the specific load capacity, wind tolerance, reach and other limitations of the lift to be used. Do not exceed these limits.
- Always be aware of what is in the travel path of the lift. Avoid electrical lines or other items within the path of travel; be aware of overhead objects as well.
- Never use aerial lift equipment in place of a crane to lift materials. Avoid oversized or awkward items on the platform or bucket; there should always be enough room for the worker to work with feet on the floor.
- Never travel with the lift raised more than what is given in the manufacturer's instructions.
- Never travel with someone elevated in the platform or bucket unless the equipment is specifically designed for that use.

(Over)



INJURY PREVENTION

Quick Review of Safety

Aerial Lifts

BEST PRACTICES

- Conduct a thorough pre-start inspection based on the lift being used. Inspect the site for hazards, both on the ground and overhead.
- Always keep your feet on the floor of the platform or bucket; do not lean over or climb on guardrails.
- Never use ladders or other equipment to further extend your height from the lift platform.
- Always use fall restraint/arrest protection on the equipment that is attached to an identified location on the platform. A body harness should be worn and connected as soon as you or any other worker enters the platform or bucket.
- Always have a thorough understanding of the specific load capacity, wind tolerance, reach and other limitations of the lift to be used. Do not exceed these limits.
- Always be aware of what is in the travel path of the lift. Avoid electrical lines or other items within the path of travel; be aware of overhead objects as well.
- Never use aerial lift equipment in place of a crane to lift materials. Avoid oversized or awkward items on the platform or bucket; there should always be enough room for the worker to work with feet on the floor.
- Never travel with the lift raised more than what is given in the manufacturer's instructions.
- Never travel with someone elevated in the platform or bucket unless the equipment is specifically designed for that use.

(Over)

- If the lift has controls on both the platform and lower unit and a worker is on the platform, the lower controls should not be operated without the express consent of the worker on the platform except in an emergency.
- Always ensure that the lift is stable before beginning work. If equipment has outriggers, they should be positioned on a solid, level surface and the brakes should be set.
- If operations require the lift to be used on an incline, wheel chocks must be used if they can be safely installed.

- If the lift has controls on both the platform and lower unit and a worker is on the platform, the lower controls should not be operated without the express consent of the worker on the platform except in an emergency.
- Always ensure that the lift is stable before beginning work. If equipment has outriggers, they should be positioned on a solid, level surface and the brakes should be set.
- If operations require the lift to be used on an incline, wheel chocks must be used if they can be safely installed.

